

DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER) BOARD AND CODE ADMINISTRATION DIVISION

PRODUCT CONTROL SECTION 11805 SW 26 Street, Room 208 Miami, Florida 33175-2474 T (786) 315-2590 F (786) 315-2599

www.miamidade.gov/economy

MIAMI-DADE COUNTY

NOTICE OF ACCEPTANCE (NOA)

Ultimate Door of Palm Beach, Inc. 2800 North 2nd Avenue Lake Worth, FL 33461

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER -Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Series Alum Clad Outswing Wood French Doors – L.M.I.

APPROVAL DOCUMENT: Drawing No. 1748, titled series "Aluminum Clad Wood Impact Out-Swing French Doors," Sheets 1 through 17 of 17, prepared by W. W. Schaefer Engineering & Consulting, P.A., dated AUG 02, 2012, signed and sealed by Warren W. Schaefer, P. E., bearing the Miami-Dade County Product Control Revision stamp with the Notice of Acceptance number and Expiration date by the Miami-Dade County Product Control Section.

MISSILE IMPACT RATING: Large and Small Missile Impact Resistant Limitations:

- 1. Max. Single partial raised panel allowed is 26"W X 32"H= 832 in² or multi-mid rails with partial raised panel not to exceed 832 in² total area.
- 2. Except where cluster anchors are specified, the #8 nail fin perimeter fasteners must not exceed 9" O.C.
- 3. Min four (4) frame screws at mullion end (Sill) are required, when tributary load width is 33-1/2" or less or when mullion span is 96" or less.
- 4. Direct Glazed Windows (DWG Ref. # 1749) by Ultimate Door are under current separate NOA.

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and series and following statement: "Miami-Dade County Product Control Approved", noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA # 12-0410.11 and consists of this page 1 and evidence pages E-1 & E-2, as well as approval document mentioned above.

The submitted documentation was reviewed by Ishaq I. Chanda, P.E.



NOA No. 14-0424.02 Expiration Date: April 16, 2016 Approval Date: July 10, 2014

Page 1

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

A. DRAWINGS

- 1. Manufacturer's parts drawings and sections(submitted under files #12-0410.11/# 11-0310.01)
- Drawing No. 1748, titled series "Aluminum Clad Wood Impact Out-Swing French Doors," Sheets 1 through 17 of 17, prepared by W. W. Schaefer Engineering & Consulting, P.A., dated AUG 02, 2012, signed and sealed by Warren W. Schaefer, P.E.
- B. TESTS (transferred from file #12-0410.11/#11-0310.01)
 - 1. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Large Missile Impact Test per FBC, TAS 201-94
 - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 - 6) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94

along with marked-up drawings and installation diagram of outswing alum clad wood French doors w/ mullions, an alum clad outswing Arch double wood door and alum clad outswing Rectangular double wood doors, prepared by Architectural Testing Lab, Test Report No. **B5667.02-450-18** dated 07/02/12, signed and sealed by Vinu Abraham, P. E.

- 2. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202–94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202–94
 - 3) Water Resistance Test, per FBC, TAS 202-94

along with marked-up drawings and installation diagram of an out-swinging wood clad aluminum French door prepared by Hurricane Test Laboratory, LLC, Test Reports No.'s HTL-0026-1008-94 and HTL-0026-0214-97, dated 11/14/94 and 01/09/97, HTL-0026-1017-99, dated 10/22/99, all signed and sealed by Timothy Marshall, P. E. and Test Laboratory, LLC, Test Report No. HTL-0026-1212-99, dated 12/08/99, signed and sealed by Vinu J. Abraham, P. E. (submitted under file # 11-0310.01)

- 3. Test reports on: 1) Large Missile Impact Test per FBC, TAS 201-94
- 2) Cyclic Wind Pressure Loading per FBC, TAS 203-94 along with marked-up drawings and installation diagram of an out-swinging wood clad aluminum French door, prepared by Hurricane Test Laboratory, LLC, Test Reports No's. HTL-0026-1023-95, HTL-0026-0508-95 and HTL-0026-1212-99, dated 1/23/95, 5/12/95 and 12/08/99, HTL-0026-0913-96, dated 06/26/97 and 09/23/96, HTL-0026-0508-95 and HTL-0026-0123-95, dated 01/23/95 and 05/12/95, all signed and sealed by Timothy Marshall, P. E. (submitted under file # 11-0310.01)
- 4. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Large Missile Impact Test per FBC, TAS 201-94
 - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 - 6) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94

along with marked—up drawings of pair of outswing wood and fixed lite (OOX) & XX/O, prepared by Hurricane Test Laboratory, LLC, Test Report No. HTL-0026-0320-97, dated 03/27/97, HTL-0026-0405-97, dated 08/27/97 and HTL-0026-0214-97 (TAS- 201), dated 05/09/97, all signed and sealed by Timothy Marshall, P. E. (transferred from file # 11-0310.02) Note: The original tests conducted were per SFBC PA 202, 201 and 203-94, now termed as FBC, TAS 202, 201 and 203-94.

Ishaq I. Chanda, P.E.
Product Control Examiner
NOA No. 14-0424.02
Expiration Date: April 16, 2016
Approval Date: July 10, 2014

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

C. CALCULATIONS (submitted under files #12-0410.11)

- 1. Anchor verification calculations and structural analysis, complying with FBC-2010, prepared by W. W. Schaefer Engineering & Consulting, P.A., dated AUG 02, 2012, signed and sealed by Warren W. Schaefer, P. E.
- 2. Glazing complies w/ ASTME-1300-02 & -04.

D. QUALITY ASSURANCE

1. Miami Dade Department of Regulatory and Economic Resources (RER).

E. MATERIAL CERTIFICATIONS

1. Notice of Acceptance No. 11-0624.04 issued to E.I. DuPont DeNemours & Co., Inc. for their "DuPont Sentry Glass ® Interlayer", expiring on 01/14/17.

F. STATEMENTS

- 1. Statement letter of conformance to FBC 2014(5th Edition) and letter of no financial interest, prepared by W. W. Schaefer Engineering & Consulting, P.A., dated April 15, 2014, signed and sealed by Warren W. Schaefer, P.E.
- 2. Statement letter, prepared by W. W. Schaefer Engineering & Consulting, P.A. dated April 10, 2014, of NOA Drawings and testing have been reviewed to 2014 FBC and found compliant and that No change to existing NOA documents are required, signed by Warren W. Schaefer, P.E.
- 3. Statement letter of conformance to FBC 2010 and letter of no financial interest, prepared by W. W. Schaefer Engineering & Consulting, P.A., dated Jul 09, 2012, signed and sealed by Warren W. Schaefer, P.E. (submitted under files 12-0410.11)
- 4. Lab compliance as part of the above referenced test reports.


G. OTHER

- 1. This NOA revises NOA # #12-0410.11, expired on April 16, 2016.
- 2. Series Un-clipped wood mullion NOA # 11-0310.02.
- 3. Test proposal, dated 03-10-11 and e-mail correspondence approval dated 08-02-12 approved by PERA.
- 4. Previous associated files are NOA(s) #11-0310.01, # 05-0824.03, 01-0327.01, 00-0912.03, 99-0317.06 and 97-0912.01.

Ishaq I. Chanda, P.E.

Product Control Examiner NOA No. 14-0424.02

Expiration Date: April 16, 2016 Approval Date: July 10, 2014



CORNER CONSTRUCTION AS DESCRIBED IN THIS DRAWING.

APPLICABLE TO OPERABLE DOORS).

3. THE SHAPES LABELED (*) ARE ONLY APPLICABLE TO FIXED PANEL DOORS (NOT

HINGE REQUIREMENTS (HALF-ROUND TOP DOUBLE DOORS)

2001.0)							
PANEL	QUANTITY						
HEIGHT	PER PANEI						
OVER 96"	4						
96" OR LESS	3						
IOTES:							
. HINGE CENT	FRLINES						

SHALL BE LOCATED APPROXIMATELY 3 1/2" BELOW FRAME SPRING-LINE, 9 1/4" ABOVE BOTTOM OF SILL

AND EQUALLY SPACED

BETWEEN. HINGE REQUIREMENTS (RECTANGULAR & EYEBROW TOP DOUBLE DOORS & ALL SINGLE DOORS)

	•	
PANEL HEIGHT	QUANTITY PER PANEL	
OVER 96"	5	
96" OR LESS	4	
IOTEC:		l

<u>NOIES:</u> 1. HINGE CENTERLINES SHALL BE LOCATED APPROXIMATELY 7 1/2" BELOW TOP OF DOOR FRAME OR BELOW FRAME SPRING-LINE, 9 1/4" ABOVE BOTTOM OF SILL AND EQUALLY SPACED BETWEEN.

FRAME ANCHOR REQUIREMENTS TABLE							
OPENING TYPE FRAME/HINGE/ FIN TO OPENING (SUBSTRATE) FASTENER TYPE		MINIMUM EMBED	MINIMUM EDGE DIST.				
FRAM	E & HINGE SCREWS	-					
MIN. 2X4 WOOD FRAME OR BUCK (MIN. GR. 3 & G=0.55)	NO. 12 SMS OR WOOD SCREW	1 1/4"	3/4"				
MIN. 16 GA. 33 KSI METAL STUD	NO. 12 GR. 5 SELF TAP/DRILL SCREW	FULL	1/2"				
MIN. 1/8" THK A36 STEEL	NO. 12 GR. 5 SELF TAP/DRILL SCREW	FULL	1/2"				
MIN. 1/8" THK 6063-T5 ALUM.	NO. 12 GR. 5 SELF TAP/DRILL SCREW	FULL	1/2"				
(2) MIN. C-90 CMU	(1) 1/4" CONCRETE SCREW	1 1/4"	2"				
2500 PSI CONCRETE	(1) 1/4" CONCRETE SCREW	1 3/4"	2"				
(2) NAILING FIN FASTENERS							
MIN. 2X4 WOOD FRAME OR BUCK (MIN. GR. 3 & G=0.55)	NO. 8 SMS SCREW	1 1/8"	1/2"				
MIN. 1/8" THK A36 STEEL	NO. 8 GR. 5 SELF TAP/DRILL SCREW	FULL	1/2"				
MIN. 1/8" THK 6063-T5 ALUM.	NO. 8 GR. 5 SELF TAP/DRILL SCREW	FULL	1/2"				
(1) CONCRETE SCREWS SHALL BE ELCO ULTRAÇONS (C.S.), ELCO CRETE-FLEX (S.S.), ITW							

RAMSET/RED HEAD TAPCONS (C.S. OR S.S.) OR HILTI KWIK-CON II (C.S OR S.S.).

(2) CMU IS NOT APPLICABLE AT THE HEAD AND SILL.

THIS SHAPE MAY BE USED AS AN -

OPERABLE DOOR ONLY IF SPRING LINE

HEIGHT ABOVE SILL IS 80" OR MORE

ALLOWABLE DESIGN ALLOWABLE DESIGN **PRESSURE** PRESSURE (ALL SINGLE & DOUBLE (SINGLE & DOUBLE SHAPED TOP RECTANGULAR OPERABLE DOORS & OPERABLE DOORS)

THEOREMOODER OF ENVIOLE DOORS &			1	LIVIDEL DO			
ALL SINGLE FIXED PANEL DOORS)			ORS)				
(2) MAX.	(2) MAX.		VABLE	MAX.	MAX.		VABLE
FRAME	FRAME	PRESSURE		FRAME	FRAME	PRES	
HEIGHT	WIDTH	(1) (PS	SF)	HEIGHT	WIDTH	(1) (PS	SF)
(IN.)	(IN.)	POS.	NEG.	(IN.)	(IN.)	POS.	NEG.
	SINGLE DOO	RS			SINGLE DOC	RS	
	43 1/2	50.0	50.0		37 1/2	50.0	50.0
	40 1/2	53.7	53.7		34 1/2	54.3	54.3
120	37 1/2	58.0	58.0	120	31 1/2	59.3	59.5
	34 1/2	63.0	63.0		28 1/2	65.0	65.0
_	32 1/2	65.0	65.0		37 1/2	55.6	55.6
	43 1/2	55.6	55.6	108	34 1/2	60.4	60.4
100	40 1/2	59.7	59.7		31 1/2	65.0	65.0
108	37 1/2	64.4	64.4		37 1/2	58.8	58.8
	36 1/2	65.0	65.0	102	34 1/2	63.9	63.9
	43 1/2	58.8	58.8		33 1/2	65.0	65.0
102	40 1/2	63.2	63.2	96	37 1/2	62.5	62.5
	38 1/2	65.0	65.0	90	35 1/2	65.0	65.0
96	43 1/2	62.5	62.5	92	37 1/2	65.0	65.0
	41 1/2	65.0	65.0		DOUBLE DO	ORS	
92	43 1/2	65.0	65.0		72	50.0	50.0
DOUBLE DOORS					66	54.5	54.5
	84	50.0	50.0	120	60	60.0	60.0
	78	53.8	53.8		55	65.0	65.0
120	72	58.3	58.3		72	55.6	55.6
	66	63.6	63.6	108	66	60.6	60.6
	64	65.0	65.0		61	65.0	65.0
	84	55.6	55.6		72	58.8	58.8
100	78	59.8	59.8	102	66	64.2	64.2
108	72	64.8	64.8		65	65.0	65.0
L	71	65.0	65.0	96	72	62.5	62.5
	84	58.8	58.8	30	69	65.0	65.0
102	78	63.3	63.3	92	72	65.0	65.0
	76	65.0	65.0	(4) 50017111			
0.0	84	62.5	62.5	(1) POSITIVE			
l 96		25.5	A= 6	LIMITED TO	TUU FOF M	INCN D	OUKO

(2) SEE LOCK OPTIONS TABLE FOOTNOTE 2 FOR FRAME SIZE RESTRICTION WHEN LOCK COMBINATION 35 & 36 ARE USED WITH ACTIVE PANEL OF DOORS.

65.0 | 65.0 | RATED.

65.0

96

92

80

(1) (2) LOC	K OPTIONS
DOUBLE DOOR ACTIVE PANEL	USE LOCK PART #31, 33 OR COMBINATION OF 35 & 36
SINGLE RECTANGULAR DOOR PANEL	USE LOCK PART #31, 33, 38 OR COMBINATION OF 35 & 36
DOUBLE DOOR INACTIVE PANEL	USE LOCK PART #32, 34 OR 36
SHAPE TOP SINGLE DOOR PANEL	USE LOCK PART #38

LIMITED TO +50 PSF WHEN DOORS

65.0 ARE TO BE WATER INFILTRATION

(1) LOCK PART #36 SHALL EXIST AT TOP & BOTTOM OF DOOR PANEL. (2) WHEN LOCK COMBINATION OF PART #35 & 36 IS USED WITH ACTIVE DOOR PANELS, FRAME SIZE OF DOOR MAY NOT EXCEED 72" WIDE X 96" TALL WITH DOUBLE DOORS NOR 37 1/2" WIDE X 96" TALL WITH SINGLE DOORS.

THESE DRAWINGS ARE APPLICABLE ONLY TO THE PRODUCT DRAWN BY SPECIFIED. THEY MAY NOT BE USED FOR THE ASSEMBLY W.R.W. AND/OR INSTALLATION OF ANY OTHER PRODUCT NOR MAY THEY BE USED FOR RATIONAL AND/OR LOCAL APPROVAL OF ANY PRODUCT NOT PRODUCED BY THE MANUFACTURES

GENERAL NOTES:

THE WOOD.

1. THESE DOOR SYSTEMS HAVE BEEN TESTED, ANALYZED & APPROVED FOR DESIGN PRESSURES NOT TO EXCEED THOSE SHOWN IN THE "ALLOWABLE DESIGN PRESSURE TABLE(S). 2. OPENINGS, BUCKING & BUCKING FASTENERS MUST BE PROPERLY DESIGNED & INSTALLED TO TRANSFER WIND LOADS TO

3. ALL HARDWARE & FASTENERS SHALL BE IN ACCORDANCE WITH THESE DRAWINGS & SHALL NOT VARY UNLESS SPECIFICALLY MENTIONED ON THE DRAWINGS. SPECIFIED ANCHOR EMBED TO BASE MATERIAL SHALL BE BEYOND WALL FINISH OR STUCCO. 4. THE DETAILS & SPECIFICATIONS SHOWN HEREIN REPRESENT THE PRODUCTS TESTED & PROPOSED FOR WATER, AIR, IMPACT,

CYCLIC & UNIFORM STATIC AIR PRESSURE TESTING IN CONFORMANCE WITH THE FLORIDA BUILDING CODE PROTOCALS TAS-201, 202 & 203 FOR LARGE MISSILE IMPACT DOORS. 5. THESE DOOR SYSTEMS HAVE BEEN DESIGNED IN ACCORDANCE WITH AND MEET THE REQUIREMENTS OF THE FLORIDA BUILDING

CODE (FBC) INCLUDING HIGH VELOCITY HURRICANE ZONES (HVHZ). 6. IMPACT SHUTTERS ARE NOT REQUIRED WITH THESE DOORS. 7. ALL ANCHORS SECURING DOOR FRAME TO PRESSURE TREATED BUCKS OR WOOD FRAMING SHALL BE CAPABLE OF RESISTING CORROSION CAUSED BY THE PRESSURE TREATING CHEMICALS IN

8. DETERMINE THE POSITIVE & NEGATIVE DESIGN LOADS TO USE WHEN REFERENCING THESE DOCUMENTS IN ACCORDANCE WITH THE GOVERNING CODE AND GOVERNING WIND VELOCITY. FOR WIND LOAD CALCULATIONS IN ACCORDANCE WITH THE FLORIDA BUILDING CODE, A DIRECTIONALITY FACTOR OF Kd = 0.85 MAY BE APPLIED PER THE ASCE-7 STANDARD.

9. NO INCREASE IN ALLOWABLE STRESS HAS BEEN USED IN THE CERTIFICATION OF THIS PRODUCT. WIND LOAD DURATION FACTOR Cd = 1.6 WAS USED FOR WOOD SCREW ANALYSIS ONLY. 10. MATERIALS, INCLUDING BUT NOT LIMITED TO STEEL SCREWS, THAT COME INTO CONTACT WITH OTHER DISSIMILAR MATERIALS SHALL MEET THE REQUIREMENTS OF FLORIDA BUILDING CODE CHAPTER 20.

11. ALL WOOD MEMBERS OF DOORS THAT MAY POSSIBLY COME INTO CONTACT WITH MASONRY OR CONCRETE SUBSTRATES, ARE SUBJECT TO MOISTURE &/OR ARE SUBJECT TO THE OUTSIDE ENVIRONMENT SHALL BE OF AN APPROVED DURABLE SPECIES OR BE TREATED IN AN APPROVED METHOD WITH AN APPROVED PRESERVATIVE PER FBC SECTION 2326.

> PRODUCT REVISED en engaging with the Florida Phone No 12-0410.11 Budding Code Expiration Date APR 16,2016

A Dade ProBuet Control

PRODUCT REVISED as complying with the Florida Acceptance No 14-0424-02 Expiration Date APRILE, 2016

ASaul Dade Prodest Coatrel

P.A. (CA 6809) CLAD ALUMINUM WINDWEER & STA ુ **≥ જ**

W.W.S.

07/09/12

ÿ

DOOR

FRENCH

OUT-SWING


IMPACT


WOOD

ULTIMATE DOOR OF PALM BEACH, 2800 2ND AVE. NORTH LAKE WORTH, FL 33461 561-642-2828

DRAWING NO. 1748 SHEET NO.

OF






EXTERIOR ELEVATION: DOUBLE RECTANGULAR DOOR

SCALE: 1/2" = 1'-0"(FRAME SCREW MOUNT CONDITION)

> SEE ALLOWABLE DESIGN PRESSURE TABLES ON SHEET 1 FOR ALLOWABLE DESIGN PRESSURES ON SINGLE & DOUBLE DOORS.



PRODUCT REVIERD

TO COMPARISON WITH the Planting
Building Code

Asseptance No 12-04/0.1

Wassed Dade Product Corner

1shungl-Chand

Dilam Dade Product Confid

07/09/12


<u>⊗</u>


DLTIMATE DOOR OF PALM BEACH, 2800 2ND AVE. NORTH LAKE WORTH, FL 33461 561-642-2828

W. SCHAEFER ENGINEERING CONSULTING, P.A. (CA 6809). 7480 150TH COURT NORTH PALM BEACH CARDENS, FL 33418 PHONE: 561-744-3424

ઇં≥ંજ

1748 SHEET NO.





MOLLI			
	GN PRE		
(SIDE	BY SIDE	DOORS	i)
MAXIMUM	MAXIMUM		
MULLION SPAN	LOAD WIDTH	PRES	
(IN.)	(IN.)	POS.	NEG.
()	51	41.2	41.2
	45	46.7	46.7
	42	50.0	50.0
120	39	53.8	53.8
120	36	58.3	58.3
		63.6	
	33 31	65.0	63.6 65.0
	54	43.2	43.2
	51	45.8	45.8
	45	51.9	51.9
108	42	55.6	55.6
	39	59.8	59.8
	36	64.8	64.8
	35	65.0	65.0
	56	44.1	44.1
	51	48.4	48.4
102	45	54.9	54.9
102	42	58.8	58.8
	39	63.3	63.3
	38	65.0	65.0
	57	46.1	46.1
	51	51.5	51.5
96	45	58.3	58.3
	42	62.5	62.5
	40	65.0	65.0
	57	49.1	49.1
	51	54.9	54.9
90	48	58.3	58.3
	45	62.2	62.2
	43	65.0	65.0
	57	52.6	52.6
٠,	51	58.8	58.8
84	49	61.2	61.2
<u> </u>	46	65.0	65.0
-	57	55.3	55.3
	54	58.3	58.3
I	h		+

MULLION ALLOWABLE

I. SEE ELEVATIONS FOR DIMENSIONING OF LOAD WIDTH. 2. ALLOWABLE UNIT PRESSURE SHALL BE THE LESSER OF THE PRESSURE SHOWN IN THIS TABLE & THAT SPECIFIED FOR THE INDIVIDUAL DOOR.


49

61.8 | 61.8

64.3 64.3

65.0 65.0

80



CHECKED BY

07/09/12

ÿ

DOOR

FRENCH

OUT-SWING

IMPACT

WOOD

CP CP CP

ALUMINUM

ULTIMATE DOOR OF PALM BEACH,
2800 2ND AVE. NORTH
LAKE WORTH, FL 33461
561-642-2828

NSULTANTS
W. SCHAEFER ENGINEERING
CONSULTING, P.A. (CA 6809)
7480 150TH COURT NORTH
PALM BEACH GARDENS, PL 33418
PHONE: 561-744-3424

ું કેશ


1748

SHEET NO. 6 or 17

GQ.

1=24

- 1. FOR ALL DETAIL NOT SHOWN, SEE INDIVIDUAL UNIT ELEVATIONS.
- 2. THERE IS NO LIMIT ON THE NUMBER OF DOORS THAT MAY BE COMBINED IN ONE DIRECTION INTO ONE OPENING PROVIDING THE OPENING IS DESIGNED TO SUPPORT ALL LOADS TRANSFERRED FROM THE DOORS & THEIR MULLIONS.
- 3. OXXO UNIT IS SHOWN. ALL OTHER FIXED/OPERABLE COMBINATIONS ALSO APPLY WITH THE MULLION CONDITIONS SHOWN.
- 4. INDIVIDUAL DOOR SIZES SHALL BE RESTRICTED AS SPECIFIED IN THE SINGLE UNIT ELEVATION.



ADDITIONAL FRAME SCREWS WHERE SHOWN AT MULLION ENDS. SEE "FRAME ANCHOR REQUIREMENTS TABLE" ON SHEET 1 FOR REQUIREMENTS (TYP. HEAD & SILL). NOTE: OUTER-MOST SCREW ON

EACH SIDE OF THE MULLION IS NOT REQUIRED WHEN LOAD WIDTH IS 33 1/2" OR LESS OR WHEN FRAME HEIGHT IS 96" OR LESS

EXTERIOR ELEVATION: DOUBLE DOORS WITH SIDE LIGHTS

SCALE: 1/2" = 1'-0"(FRAME SCREW MOUNT CONDITION)

(RECTANGULAR DOORS SHOWN, SHAPED DOORS ALSO APPLY, SEE "APPROVED SHAPES" TABLE ON SHEET 1)

> SEE "MULLION ALLOWABLE DESIGN PRESSURE" TABLE ON SHEET 6 FOR ALLOWABLE DESIGN PRESSURES ON MULLED UNIT

MULTIPLE UNIT NOTES:

1. FOR ALL DETAIL NOT SHOWN, SEE INDIVIDUAL UNIT ELEVATIONS.

- 2. THERE IS NO LIMIT ON THE NUMBER OF DOORS THAT MAY BE COMBINED IN ONE DIRECTION INTO ONE OPENING PROVIDING THE OPENING IS DESIGNED TO SUPPORT ALL LOADS TRANSFERRED FROM THE DOORS & THEIR MULLIONS.
- 3. OXXO UNIT IS SHOWN. ALL OTHER FIXED/OPERABLE COMBINATIONS ALSO APPLY WITH THE MULLION CONDITIONS SHOWN.
- 4. INDIVIDUAL DOOR SIZES SHALL BE RESTRICTED AS SPECIFIED IN THE SINGLE UNIT ELEVATION.

PRODUCT REVISED as complying with the Florids Acceptance No 14-042402 Buiding Code Expiration Date 4/16/16

14horal Chans Mani Dade Product Control


PRODUCT REVIEWD in wasplying with the Florida Budding Code Asseptance No 12 Papiration Bate 4774117

Mand Date Priday Carry

	BY DATE						
	à						
	NO. REVISION DESCRIPTION						
	Š						
2	CLAD WOOD IMPACT OUT-SWING FRENCH DOOR		MANU	ULTIMATE DOOR OF PALM BEACH, INC.			561-642-2828
	DRAWING TITLE ALUMINUM CLAD WOOD		CONSULTANTS	W. W. SCHAEFER ENGINEERING	& CONSULTING, P.A. (CA 6809	7480 150TH COURT NORTH	PHONE: 561-744-3424
	CERTIFICATION				AUG 6 9 2012	702 2	WARREN W. SCHAEFER, P.E.
	O:	rai 1	74	_{в н}	io.	R	EV.


SHEET NO. 7 of 17

CHECKED BY: W.W.S. DATE: 07/09/12




FOR A STRAIGHT FRAME.

SEE ALLOWABLE DESIGN PRESSURE TABLES ON SHEET 1 FOR ALLOWABLE DESIGN PRESSURES ON FIXED PANEL DOORS.



1748 SHEET NO. 8 of 17




EXTERIOR ELEVATION: SINGLE FIXED PANEL DOOR

SCALE: 1/2" = 1'-0"(FRAME SCREW MOUNT CONDITION)

RECTANGULAR FIXED PANEL SHOWN. SHAPE TOP CONDITION ALSO APPLIES WITH ANCHORING ALONG THE FRAME CIRCUMFERENCE BEING THE SAME AS SPECIFIED FOR A STRAIGHT FRAME.

> SEE ALLOWABLE DESIGN PRESSURE TABLES ON SHEET 1 FOR ALLOWABLE DESIGN PRESSURES ON FIXED PANEL DOORS.



EXTERIOR ELEVATION; QUAD PANEL DOOR WITH FIXED ASTRAGALS IN ONE FRAME

SCALE: 1/2" = 1'-0"(FRAME SCREW MOUNT CONDITION)

ALLOWABLE DESIGN PRESSURE (DOORS WITH FIXED ASTRAGALS) +48/-59 PSF

FIXED ASTRIGAL UNIT NOTES:

- OXXO UNIT IS SHOWN. OX, XO, OXO, XXO & OXX UNITS ALSO APPLY.
- FOR DETAIL NOT SHOWN, SEE INDIVIDUAL UNIT ELEVATIONS.

FRODUCT REVISED us complying with the Florida Buiding Code Acceptance No 14-0424.02. Expiration Date 4/16/16 Mari Dade Frederi Control

PRODUCT REVISED in comparing with the Florida Ruiding Code Assentance No 12-0410-1 Expiration Date WILL 16 Mani Dade Product Control

W. SCHAEFER ENGINEERING CONSULTING, P.A. (CA 6809)
7480 150TH COURTH
PALM BEACH GARDENS, PL 33418
PHONE: 561-744-3424 2012 N

WOOD


CLAD


DATE: 07/09/12


ULTIMATE DOOR OF PALM BEACH, 2800 2ND AVE. NORTH LAKE WORTH, FL 33461 561-642-2828


1748 SHEET NO.


9 of 17


















ITEM #	I	MANUFACTURER/NOTES
	PARTS	
1	JAMB	WOOD
2	HEAD RAIL & HINGE, INACTIVE & FIXED PANEL STILES	WOOD
3	BOTTOM RAIL	WOOD
4	HINGE & FIXED PANEL STILE	WOOD
5	ASTRAGAL	WOOD
6	MULLION	WOOD
7	GLAZING BEAD (MONOLITHIC GLASS)	WOOD
8	GLAZING BEAD (INSULATED GLASS)	WOOD
9	GLAZING BEAD (RAISED PANEL)	WOOD
10	MID-RAIL	WOOD
14	JAMB CLADDING	6063-T5 ALUMINUM
15	TOP RAIL & STILE CLADDING	6063-T5 ALUMINUM
16	BOTTOM RAIL CLADDING	6063-T5 ALUMINUM
17	THRESHOLD BASE	6063-T5 ALUMINUM
18	THRESHOLD BASE COVER	6063-T5 ALUMINUM
19	ASTRAGAL	6063-T5 ALUMINUM
20	TOP RAIL & STILE GLAZING BEAD	6063-T4 ALUMINUM
21	BOTTOM RAIL GLAZING BEAD	6063-T5 ALUMINUM
22	MULLION CLIP	6063-T5 ALUMINUM
23	MID-RAIL CLADDING	6063-T5 ALUMINUM
25	SUB-SILL .	PVC
	HARDWARE	
30	4 1/2" X 4 1/2" BUTT HINGE	HAGER 1191 BRASS WITH S.S. BALL BEARINGS
31	3-POINT LOCK SYSTEM (SHOOT BOLTS & DEADBOLT)	ULTIMATE DOOR UD120A
32	2-POINT LOCK SYSTEM (SHOOT BOLTS)	ULTIMATE DOOR UD120B
33	3-POINT LOCK SYSTEM (SHOOT BOLTS & DEADBOLT)	HARDKING SS963 MODIFIED
34	2-POINT LOCK SYSTEM (SHOOT BOLTS)	HARDKING SS963 MODIFIED
35	DEADBOLT	SCHLAGE B100 OR EQUIVALENT
36	FLUSH BOLT	HAGER BRASS 282D
37	HANDLE	AS REQUIRED TO OPERATE LOCK
38	4-POINT LOCK SYSTEM (TONGUE BOLTS & DEADBOLT)	SCHLEGEL FFNS-3300
	SEALS & SEALANTS	<u> </u>
40	TOP SWEEP	PREFERRED PLASTICS EPDM ULTIL 9483360092
41	KERF WEATHERSTRIP	SCHLEGEL QLON QEBD 875
42	THRESHOLD CAP WEATHERSTRIP	PREFERRED PLASTICS EPDM GTCWL 9421815012
43	BOTTOM SWEEP	PREFERRED PLASTICS EPDM ULTIL 9411357562
44	FIXED STILE BULB WEATHERSTRIP	PEMCO SILICONE S88W510
45	HINGE WEATHERSTRIP	PREFERRED PLASTICS SILICONE ULTIL 9430965012
46	PANEL BULB WEATHERSTRIP	SCHLEGEL THERMOPLASTIC AP-425
47	GLAZING TAPE 1/16" X 7/8"	SAINT GOBIAN V2862
48	GLAZING TAPE 1/16" X 1/2"	SAINT GOBIAN V2862
49	GLAZING TAPE 1/16" X 1/4"	SAINT GOBIAN V2862
50	FIXED PANEL TOP WEATHERSTRIP	PEMKO VINYL V41GR
	,	

1751 #	TEM RECODICTION	T	DRAWN	BY:	_
ITEM #	ITEM DESCRIPTION	MANUFACTURER/NOTES	PLOT:	R.U.	_
	FASTENERS			=2	
	NO. 6 X 3/4" SMS	3" FROM CORNERS & 12" MAX. O.C.			١
-	NO. 6 X 3/4" SMS	2" FROM ENDS & 16" MAX. O.C.	DATE		
	NO. 8 X 2 1/2" WOOD SCREW	3" FROM CORNERS & 9" MAX. O.C.		┼	╀
	NO. 10 X 3 1/2" WOOD SCREW	3" FROM CORRNERS & 9" MAX. O.C.	8		
57	NO. 12 X 1" S.S. SMS SCREW	3 PER HINGE		+	╁
58	NO. 12 X 1 1/4" S.S. SMS SCREW	4 PER HINGE	Š		
59	NO. 7 X 2 1/4 WOOD SCREW	1 1/2" FROM ENDS & 11" MAX. O.C.	Ë	ŀ	
60	NO. 6 X 1 5/8" WOOD SCREW	2" FROM CORNERS & 9" MAX. O.C.	DESCRIPTION		
61	3/8" X 6" GALV. LAG BOLT WITH 1/4" WASHER	2 PER FIXED PANEL DOORS	2		1
62	NO. 12 X 2" S.S. SMS SCREW	1 PER HINGE	REVISION	ļ.	l
NOTE: \	WOOD USED IN TESTING WAS PONDEROSA PINE WITH A S	PECIFIC GRAVITY OF G = 0.43 AND A	8	ŀ	1
ì	MODULUS OF ELASTICITY OF $E = 1,200,000$ PSI. OTHER	WOOD SPECIES APPLICABLE FOR USE WITH	ģ	十	t
	HIS PRODUCT ARE THOSE WITH A SPECIFIC GRAVITY OF	0.43 AND MODULUS OF ELASTICITY OF	Z	┿	Ļ
. 1	,200,000 PSI OR GREATER. ALL WOOD IS MINIMUM GRAD	DE 2 MILLED BY ULTIMATE DOOR TO SELECT.		ı	
-	3.875 4.560 -			ı	e
	<u> </u>	94		ı	2
	KEMOVE FLANGE	0.585	꽃	ı	Ì
	AS REQ'D		DOOR	ı	ž
Los	2.100 (15) TOP RAIL & STIL	E CLADDING	1!	ı	۵
			ENCH	ı	7
0.100 →		− 7.507 −−−			č



PRODUCT REVISED

as complying with the Florida

Building Code

Acceptance No 14-0424-02

Expiration Date ATA 15-2016

Mind Dide Product Control

□ 0.500

25 SUB-SILL

LESTIFICATION ALUMINUM CLAD WOOD ALUMINUM CLAD WOOD CONSULTANTS

S. CONSULTANTS

W. W. SCHAEFER ENGINEERING

CONSULTING, P.A. (CA 6809)

7480 150TH COURT NORTH
PALM BEACH GARDENS. P. 33418

PALM BEACH GARDENS. P. 33418

PALM BEACH GARDENS. P. 33418

CHECKED BY: W.W.S.

DATE: 07/09/12

<u>≥</u>

THE ALUMINUM CLAD WOOD IMPACT OUT-SWING FRENCH DOOR

F PALM BEACH, 1 AVE. NORTH TH, FL 33461 542-2828

ULTIMATE DOOR OF F 2800 2ND AV LAKE WORTH, 561-642